

**SAFETY INSPECTION/FUNCTION CHECKOFF SHEET FOR PRIVATELY OWNED
FIREARMS BROUGHT TO NORTHWOODS SCOUT RESERVATION**

A licensed gunsmith must check all privately owned firearms before being brought to camp using this form. Chief Okemos Council will not allow firearms not meeting this requirement to be used on the range at any time.

Name of Owner _____

Address of Owner _____ City _____

State _____ Zip _____ Home Phone _____

Make of gun _____ Model _____

*Gauge/Caliber _____ Serial Number _____

**Shotguns must be either 12 gauge or 20 gauge. No other gauges are acceptable for use at camp because of the increased potential of using incorrect ammunition with gauges that are closer together in size. Also, the camp only stocks ammunition in those gauges. Privately owned ammunition will not be allowed on the range at any time. Rifles must be single shot .22 long rifle only.*

Date of Inspection _____

Trigger Pull: NO RELEASE TRIGGER OK _____ Initial _____

Trigger Pull Weight Oz./Lbs. _____ Initial _____
(Must be above 3 lbs.)

Type of Action: Pump _____ *Semi Auto Gas _____ **Semi Auto Recoil _____

- For Semi Auto Gas – If Gas operated is “O” Ring (gas seal) OK? _____
- ** For Semi Auto recoil operated, are rings set correctly for light loads? _____

NO BREAK OPEN OR EXPOSED HAMMER GUNS ARE PERMITTED

Firing Pin check: Measurement in Thousands _____

Enough protrusion to reliably ignite primers? _____

Does firing pin move freely without binding? _____

Does firing pin retract on its own? _____

Does firing pin stick in the fire position? _____

Function Test:

The following must be performed with live ammunition. With the action open, drop a light trap or skeet load onto the ejection port. With the safety off, close the bolt and chamber the round. Gun must not fire on closing. Engage the safety and ascertain that the gun will not fire by pulling the trigger or tapping the butt stock on a hard surface (simulate being dropped on the butt). Release the safety and fire the gun by pulling the trigger. Ascertain that the action cycles appropriately, extracting and ejecting the empty case and leaving the action with the bolt open and the loading area visible. (Semi Autos must cycle leaving the bolt locked open using light trap or skeet loads.)

Signature of Gunsmith _____ Date _____